



MaxiCharger Single Charger A07 Series

Innovating AC Charging Solutions



One-Click Snap-in
Installation



Support OCPP1.6J
OCPP2.0.1



APP,RFID Card
Mobile Payment



Digital Twin
O&M Platform



Green Energy
Integration

Technical Specifications

Product Information

AC Power Output Rating	7.4kW
Model	EW07-C050000A002
SKU	106002078
Input/output voltage	230V~±15%,1-phase,50/60Hz
Circuit Breaker Options (A)	40A
Input power connections	1P+N+PE 50/60Hz
Network type	TN,TT, IT
Input cord	Hardwired
Connector type	IEC 62196 Type 2 with 5m Cable
Ground fault detection	AC 30mA + DC 6mA
Protection	Overcurrent, Overvoltage, Undervoltage, Integrated Surge protection
Card reader	ISO 15693, ISO 14443 A/B
Vehicle communication	-
Metering Accuracy	NMI, ±1%
Authentication methods	RFID, Apps

General Characteristics

Enclosure rating	IP65, IK10,Indoor or Outdoor installation
Operating altitude	2000m
Operating temperature range	-30°C~50°C
Storage temperature range	-40°C~70°C
Mounting	Wall mounted or floor using a pedestal
Dimensions (H×W×D)	315*170*117mm
Operating Humidity	<95%, Non-Condensing
Weight	Approx.5.8kg

User Interface

User interface	Autel Charge APP, Autel Charge Cloud
Connectivity	Wi-Fi, Bluetooth
Status indication	LEDs
Communication protocols	OCPP 1.6J, OCPP 2.0.1(Core, Advanced Security)
V2G(Vehicle-to-Grid)	-

Software Update

Software update	OTA updates via web portal
-----------------	----------------------------

Certification and Standard

Certifications & Compliance	CE, IEC /EN 61851-1, IEC 61008-1-A1, IEC 62955-1-A1, IEC 62196-2, EMC Class B, RCM, NMI 14/4/0
Lifespan	10+ Years
Warranty	5 Years